

TECHNICAL DETAILS**ENGINE**

Design	1-cylinder 4-stroke engine, water-cooled
Displacement	373.2 cm ³
Bore	89 mm
Stroke	60 mm
Performance	32 kW (43 hp)
Starting aid	Electric starter
Transmission	6 speed, claw shifted
Engine lubrication	Wet sump
Primary gear ratio	30:80
Secondary gear ratio	15:45
Cooling system	Liquid cooling system, continuous circulation of cooling liquid with water pump
Clutch	Wet multi-disc clutch / mechanically operated
Ignition system	Contactless, controlled, fully electronic ignition system with digital ignition timing adjustment

CHASSIS

Frame	Tubular space frame made from steel, powder-coated
Fork	<i>WP Suspension</i> Up Side Down
Shock absorber	<i>WP</i> Monoshock
Suspension travel front	125 mm
Suspension travel rear	150 mm
Brake system Front	Disc brake with four-pot brake caliper
Brake system Rear	Disc brake with one-pot brake caliper, floating brake discs
Brake discs - diameter Front	300 mm
Brake discs - diameter Rear	230 mm
Chain	5/8 x 1/4" X-Ring
Steering head angle	66.5°
Wheel base	1,340±15 mm
Ground clearance (unloaded)	178.5 mm
Seat height (unloaded)	820 mm
Total fuel tank capacity approx.	10 l Unleaded premium fuel (95 RON)
dry weight	147 kg